

Micro



THE HEATING SOLUTION FOR ABOVE GROUND POOLS



For above
ground pools



Silent



As low as 10 °C



R32



ASSETS

- Ideal for above ground pools
- Heating mode only
- Painted galvanized sheet enclosure
- Operates at an ambient temperature as low as 10°C
- Silent
- Application dedicated with bluetooth connection to control your heat pump

NEW



- User interface
- 32 / 38" fittings



All your parameters are managed
by a dedicated free application
(Bluetooth connection)



TUTO

Watch the video

Description	Unit	HP2021DT3C	HP2031DT3C
MICRO			
Voltage		230V~ 50 Hz	
Heating capacity*	kW	2.5	3.5
COP*		4.12	5.12
Input power*	kW	0.6	0.68
Current Intensity*	A	2.7	2.95
Heating capacity**	kW	1.5	2.23
COP**		2.54	3.53
Input power**	kW	0.58	0.63
Current Intensity**	A	2.53	2.74
Operation mode		Heating only	
Compressor type		Rotary	
Fan quantity		1	1
Fan speed	RPM	700	700
Fan direction		Axial	
Pressure noise level (at 1 meter)	dB(A)	46	46
Water connection	mm	32/38	32/38
Water Flow	m³/h	1.1	1.6
Water pressure drop (max)*	kPa	0.8	1.2
Gas / kg	kg	R32 / 0.160	R32 / 0.250
T.eq CO ₂		0.11	0.17
Net Weight	kg	24	27
Gross Weight	kg	27	30
Net dimensions	mm	418 × 399 × 420	418 × 399 × 420
Gross dimensions	mm	450 × 430 × 430	450 × 430 × 430
Pool Water volume***	m³	<15m³	<20m³
EAN		3660149613287	3660149613294

* Conditions: Air @27°C HR 80% Water 26°C. ** Conditions: Air @15°C HR 70% Water 26°C.

*** As an indication, suitable for private pools equipped with a thermal cover from mid May to mid September and for a minimum ambient temperature of 15 °C.

