



SIMPLE AND
LONG-LASTING

Ei²

1 LONG-LASTING

One of the **longest-lasting** chlorinators in its category (up to 7,500 hours) thanks to its **high quality titanium** electrode.

Ti²²
**TITANIUM
INSIDE**

2 SUITABLE FOR ALL INSTALLATIONS

The compact cell and watertight IPX5 casing allow the Ei² to be installed anywhere, **in confined spaces and even in humid environments.**


**EASY
INSTALLATION**

3 FAST INSTALLATION

Ei² can be installed in **just 10 minutes** in any environment, thanks to its **patented Quick Fix system.**




SPECIFICATIONS



NO MAINTENANCE

Self-cleaning electrodes via reverse polarity.



SHUTTER MODE

Automatic reduction of chlorine production when the pool's roller shutters are closed (adjustable to 0% or 20%).

STOP

SAFE-SYSTEM

Automatic stop if there is no flow in the cell.



WATERPROOF

The "IPX5" waterproof control unit can be installed in all types of machine rooms.

UNCONDITIONAL
GUARANTEE
UNCONDITIONAL

UNCONDITIONAL GUARANTEE

On the control box and the cell, whatever the causes of damage.

FOR WHICH TYPE OF POOLS?

1 ALL TYPES OF SWIMMING POOLS



2 POOLS UP TO 90M³ (TEMPERATE CLIMATE, FILTRATION 8 HR/DAY)



STANDARD FEATURES



Cell installation kit for 50-mm and 63-mm hoses

TECHNICAL INFORMATION

MODELS	Ei ² 12	Ei ² 20	Ei ² 25
Volume of water treated (temperate climate, filtration 8hr/day)	50 m ³	90 m ³	110 m ³
Nominal chlorine production	12 g/h	20 g/h	25 g/h
Power rating	70 W	110 W	140 W
User interface	LEDS		
Operating mode	Normal, Shutter mode (0-20%)		
Clock/Timer	Linked to the filtration		
Reverse polarity	Yes: 5 hr		
Recommended salt level - minimum	4 g/L - 3.0 g/L minimum (*)		
Safety	'Low salt' indicator light: reduced production to protect the electrode 'No flow' indicator light: production is interrupted until optimal conditions return		
Cell position	Horizontal		
Compatible pipework	DN50, DN63, 1½" (48 mm)		
Protection rating	IPX5		
50 Hz power supply	220-240 VAC (mains power cable with moulded plug)		

AVAILABLE ACCESSORIES



Locking ring wrench



Winterizing cap

Salt chlorinators are an **automatic and efficient** disinfection solution. **They are easy to use**, offer complete water treatment and **reduce maintenance**.

2 YEAR
UNCONDITIONAL
WARRANTY